

---

## Flush Mounted Electro-Magnetic Fire Door Holder - 24v DC - With Manual On / Off Switch - Supplied With Armature Plate - Polished Chrome

### Product Images

---



### Description

---

Polished chrome finish electro-magnetic door holder.

Flush mounted, back box is designed to be rebated into the wall.

The use of the Electro-magnetic door holder is the only safe and legally compliant way (with respect to ADM and BS 8300) to hold fire doors open within a building.

The Wall Magnet is also linked directly to the buildings Fire Detection system so that in the event of a fire, all doors are automatically released from the hold open position and shut to prevent the spread of fire and smoke throughout the building.

**Specification:** Electro-Magnetic Door Holder; Incorporating a manual On / Off switch; Designed to be surface mounted to a wall; Can be fitted direct to walls or floor mounted

<b>Standard Voltage</b>	24 Volt DC
<b>Resistance</b>	330 Ohms
<b>Power</b>	1.75 Watts
<b>Power Range Suitability</b>	3-7 in accordance with BS EN 1154

	<b>Width</b>	<b>Height</b>	<b>Depth</b>
<b>Box Dimensions</b>	86 mm	86 mm	52mm
<b>Armature Dimensions</b>	57 mm	57 mm	19 mm

**Material:** Manufactured from British Extruded Aluminium and British Steel

**Fire Tested:** 120 Minutes

**Standards**


- BSEN 1155 (Electrical)      BSEN 1154 (Mechanical)
- BSEN 1634 (Fire Test)      BS8300 (Ease of Access)

CE Marked / UKCA Marked

**Finish** - polished chrome face plate

**Products in this set**

---



**43502.1 - Flush Mounted Electro-Magnetic Fire Door Holder - 24v DC - With Manual On / Off Switch - Supplied With Armature Plate - Polished Chrome**