

G Johns & Sons Ltd Unit D Westside Business Centre Flex Meadow Harlow, Essex CM19 5SR www.gjohns.co.uk 020 8360 7771 sales@gjohns.co.uk VAT No: GB232661872 Company No: 00384076

Flush Mounted Electro-Magnetic Fire Door Holder - 24v DC - With Manual On / Off Switch - Supplied With Armature Plate - Polished Chrome

Product Images





Description

Polished chrome finish electro-magnetic door holder.

Flush mounted, back box is designed to be rebated into the wall.

The use of the Electro-magnetic door holder is the only safe and legally compliant way (with respect to ADM and BS 8300) to hold fire doors open within a building.

The Wall Magnet is also linked directly to the buildings Fire Detection system so that in the event of a fire, all doors are automatically released from the hold open position and shut to prevent the spread of fire and smoke throughout the building.

Specification: Electro-Magnetic Door Holder; Incorporating a manual On / Off switch; Designed to be surface mounted to a wall; Can be fitted direct to walls or floor mounted

Standard Voltage	24 Volt DC
Resistance	330 0hms
Power	1.75 Watts
Power Range Suitability	3-7 in accordance with BS EN 1154

	Width	Height	Depth
Box Dimensions	86 mm	86 mm	52mm
Armature Dimensions	57 mm	57 mm	19 mm

Material: Manufactured from British Extruded Aluminium and British Steel

Fire Tested: 120 Minutes

Standards

BSEN 1155 (Electrical)	BSEN 1154 (Mechanical)
------------------------	------------------------

BSEN 1634 (Fire Test) BS8300 (Ease of Access)

CE Marked / UKCA Marked

Finish - polished chrome face plate

Products in this set

×

43502.1 - Flush Mounted Electro-Magnetic Fire Door Holder - 24v DC - With Manual On / Off Switch - Supplied With Armature Plate - Polished Chrome