


Automatic Electronic Sliding Door Track System - For Bi-Parting Internal Double Glass Doors Up To 1058mm Wide - 40kg Max Door Weight

Product Images



Description

- Automated electronic sliding door gear system for bi-parting glass double doors up to 40kg in weight (per door)
- The glass sliding doors can be opened by the push of a wall mounted button (supplied as standard), remote control or by activation of a movement sensor – offering the utmost in sophistication and convenience
- Designed for use in residential properties including bathrooms and en-suites.
- Glass doors attach to the track via clamps (no need to drill or cut the glass).
- Exceptionally smooth and reliable automatic system.
- Includes push and go, configurable closing speeds and an auto closing delay timer.
- Works as regular sliding doors in the event of no power.
- Obstacle detection and safe low voltage operation.

- Supplied with two wall mounted control panels.
- Can be soffit (ceiling) fixed or face (wall) fixed as standard.
- Each set includes all the main components needed to install a long lasting, smooth running electronic automated sliding door track for glass double doors.
- Suitable for internal glass doors only.
- **Doors not included.**
- **Please note this kit should not be used to operate doors that are subject to building regulations such as fire doors, smoke control doors, escape doors or doors on escape routes. Suitable for domestic use only.**

Alternative Kits Available:

- Single door kit for glass doors - **see related product - 43522**
- Single door kit for wooden doors - **see related product - 43520**
- Bi-parting double door kit for wooden doors - **see related product - 43521**

Standard Operation Options

- **Push and go** - the sliding door kit can be configured so that the door only needs to be pulled / pushed open a small amount before the automation takes over to open the door / close the door. **This option is included as standard.**
- **Adjustable closing speeds** - the closing / opening speeds of the doors can be adjusted. **This option is included as standard.**
- **Auto closing delay timer** - a timer can be set so that the doors automatically closes after being opened. **This option is included as standard.**
- **Wall mounted button** - a simple push of a button will automatically open / close the sliding doors. **2 x Wall mounted buttons are included as standard**

Alternative Operation Options


- **Remote control** - a wire-free option to remotely open and close the sliding doors - **see related product - 43524.1**
- **Motion sensor** - a radar sensor that detects motion, allows the sliding doors to automatically open when a user walks up to it - **see related product - 43525.1**

Drive Unit Specification

- Operation Voltage: 24V safety – low voltage via external power unit.
- Maximum Operating Speed: 26 cm/s variable.
- Running Performance: Soft start and stop.
- Safety Function: Includes obstacle detection in both directions.

Double Sliding Door Kit


Sliding Double Doors



Dimensions And Track Lengths Available

Item Code	Maximum Width Door	Minimum Width Door	Overall Track Length	Maximum Door Weight (W)	Door Thickness
43523.1	1058mm*	760mm	4000mm (2 x 2000mm)	40kg (Per Door)	10mm
43523.2	1058mm*	760mm	4000mm (2 x 2000mm)	40kg (Per Door)	12mm

* Maximum clear opening width 2035mm




Fixing Options

- Ceiling / soffit mounted - track is pre-drilled to allow for ceiling mounting as standard.
- Wall / surface mounted - this kit is supplied with brackets that attach to the top of the track to allow for wall mounting.


OH = OPENING HEIGHT
 TC = TOP CLEARANCE
 BC = BOTTOM CLEARANCE
 P = PACKER

B = DOOR THICKNESS
 TSH = TRACK SET HEIGHT
 X = OVERLAP (PCH)
 RECOMMEND 13mm



Floor Guide

- Supplied with "U" shape floor guides, fixed to the floor next to the door frame, this helps to guide the door insuring it runs straight.



Items Included Within The Automated Electronic Sliding Door Track Kit Fo Single Doors

- 2 x 2000mm length aluminium tracks
- 4 x Glass door clamps
- 4 x Track stops
- 1 x Toothed belt
- 1 x Belt clamp
- 1 x Tension wheel
- 8 x Face fix brackets
- 1 x Motor (with 1.5m cable length)
- 1 x 24V transformer
- 2 x Wall mounted control panel buttons

Important Information Before You Purchase

- The installation is intended to be carried out by professionally competent personnel only. The mounting must be done by technically educated, trained and qualified personnel. Electrical wiring's have to be completed by a suitably qualified specialist.
- The installation instructions detail how the system can be safely installed, to comply with the appropriate European Standards and allow the installer to 'CE mark' the system once complete.
- The specifications must be respected, especially maximum weight restriction of the door leaf. Any other use of this product is considered inappropriate use. It is not guaranteed that this product will work in combination with fittings, motors or other electronic devices supplied by other manufacturers.
- **This kit should not be used to operate doors that are subject to building regulations such as fire doors, smoke control doors, escape doors or doors on escape routes.**

Products in this set



43523.1 - Automated Electronic Sliding Door Track System - For Bi-Parting 10mm Thick Glass Double Doors Between 760mm - 1058mm Wide - 4000mm Track Length - 80kg Max Door Weight - Supplied With 2x Control Panels



43523.2 - Automated Electronic Sliding Door Track System - For Bi-Parting 12mm Thick Glass Double Doors Between 760mm - 1058mm Wide - 4000mm Track Length - 80kg Max Door Weight - Supplied With 2x Control Panels