

G Johns & Sons Ltd Unit D Westside Business Centre Flex Meadow Harlow, Essex CM19 5SR www.gjohns.co.uk 020 8360 7771 sales@gjohns.co.uk

#### Flush Fitting Pull Out Ring Handle - Squash Court Style Door Handle - Polished Stainless Steel

#### **Product Images**



- Flush fitting pull out ring style door handle, inset design ideal for use on doors that need to fold back against a wall.
- Also known as a squash court handle, this style of door handle is often found on squash court doors as it sits completely flush with the face of the door. (Flush style means nothing projects from the door for a player or ball to hit.)
- Designed to work with a tubular latch this item can be used as a working door handle.
- 8mm follower built into back of the ring handle to suit a UK standard 8mm x 8mm spindle.
- Designed to be morticed (cut) into the face of a door so it sits flush with the surface.
- Shallow design only 11mm thick if fitting completely flush.
- Made from stainless steel this item is a brushed satin finish.

### Size Details



Item Code Height Width Recess DepthRecess DiameterBackplate ThicknessRing Pull Size (Internal Dimension)

43532.1 90mm 90mm 8mm 72mm 3mm	45mm
--------------------------------	------

#### **Base Material**

• Made from stainless steel.

## **Finish Details**

• Polished stainless steel - (shiny finish).

### **Alternative Finishes Available**

• Satin stainless steel - (brushed finish).

# Fixings

• This handle is fitted via 4 x countersunk wood screws through the face of the backplate.

## Usage

- If fitting two flush pulls to a door (one either side) in conjunction with a tubular latch the minimum thickness door required is 35mm.
- Suitable for internal or external use.

# **Unit Of Sale**

• This item is sold individually - (Each)

#### Products in this set



43532.1 - Flush Fitting Squash Court Style Door Handle - Polished Stainless Steel - Each