

G Johns & Sons Ltd Unit D Westside Business Centre Flex Meadow Harlow, Essex CM19 5SR www.gjohns.co.uk 020 8360 7771 sales@gjohns.co.uk

Multipoint Door Lock Set For External Timber / Wooden Double Doors 44mm To 57mm Thick - Lift Handle To Lock Operation

Product Images





Description

- Multipoint door lock set for external double timber / wooden doors.
- 7 point locking 2 x hooks,1 x dead bolt, 4 x shoot bolts and 1 x latch,
- "Lift handle to lock" operation on both master and slave doors.
- Sold as a set which includes: main lock, slave lock, top & bottom bolts (x4), dead lock keeps (x4) and door latch strike plate.
- Must be used in conjunction with 2 x pairs of multi-point door handles and 2 x Euro profile cylinders SOLD SEPARATELY.
- Options available to suit 44mm and 54mm thick doors.
- As standard these locks are suitable for doors up to 2115mm in height but can be extended to suit doors up to 2600mm in height by purchasing the extension rod **43964.1**

Operation

- The slave door is locked via top and bottom shoot bolts which are activated and withdrawn via the use of multi-point door handles from either side of the door (handles sold separately). A Euro profile cylinder is then used to lock the shoot bolts in place (Euro cylinder sold separately).
- The master lock securely engages into slave mechanism.
- The hook bolts on the master lock are engaged and withdrawn via multipoint lever handles from either side of the door (handles sold separately).
- The deadbolt on the master lock is locked and un-locked via a Euro profile cylinder (sold separately).

Features

- No need for false (dummy) mullion.
- Suitable for use on left or right handed doors.
- Suitable for inward or outward opening doors.
- Medium weight springing, designed for use with spring assisted (sprung) door handles.
- Bolt through facility for standard multipoint door handles.
- 8mm x 8mm spindle follower (to suit standard UK size spindles).
- Latch can be reversed on site without taking the lock case apart.

Security Level

- Medium security architectural range.
- Suitable for use on external doors in residential properties

Finish

• Stainless steel forend.

Dimensions

ltem Code	Lock Case Depth	Backset To Keyhole	Euro Centres	Door Thickness	Minimum Door Height	Max Door Height *
43963.1	63mm	45mm	92mm	44mm	1830mm	2115mm*
43963.2	63mm	45mm	92mm	54mm	1830mm	2115mm*

* Height can be extend to suit doors up to 2600mm by using extension rod 43964.1

Unit Of Sale

• Double door kit which includes the following components:

- $\circ~$ 1 x Master door multipoint lock (with 2 x hook bolts, latch and dead bolt).
- $\circ~$ 1 x Slave door multipoint lock (with top and bottom shoot bolts).
- \circ 4 x Shoot bolts (2 x top & bolts for the master door lock and 2 x top & bolts for the slave door lock).
- 4 x Shoot bolt keeps.
- 1 x Latch strike plate,

Products in this set

×

43963.1 - Multipoint Door Lock Set For External Double Doors - 92mm Euro Centres - 45mm Backset -Door Heights 1830mm - 2115mm - To Suit 44mm Thick Doors

43963.2 - Multipoint Door Lock Set For External Double Doors - 92mm Euro Centres - 45mm Backset -Door Heights 1830mm - 2115mm - To Suit 54mm Thick Doors