

G Johns & Sons Ltd Unit D Westside Business Centre Flex Meadow Harlow, Essex CM19 5SR www.gjohns.co.uk 020 8360 7771 sales@gjohns.co.uk VAT No: GB232661872 Company No: 00384076

# 3 Lever Economy Mortice Sash Lock - CE / UKCA Marked - Fire Rated - Certifire Approved - Brushed Satin Nickel

#### **Product Images**





#### **Description**

- 3 lever economy range sash lock, with a satin (brushed) nickel finish.
- Basic style 3 lever cut keys low level security.
- For use on doors that require door handles and need to be locked via a standard "chubb" style key.
- Must be used in conjunction with some form of door handle.
- Comes supplied with a satin nickel forend and frame mounted strike plate.

# **Operation**

- The latch is withdrawn via a lever handle from either side of the door (handles sold separately).
- Deadbolt is locked and unlocked via the supplied cut keys.

#### **Features**

- Solid brass deadbolt and latch.
- Medium weight spring strength ideal for use with sprung lever furniture.
- Bolt through facility for bolt-together fixing lever handles and accessories at 38mm centres.
- 8mm x 8mm spindle follower (to suit standard UK size spindles).
- Patented latch reversal mechanism. Latch can be reversed on site without taking the lock case apart.
- Reversible and adjustable strike plate.

# **Security Level**


- Low security economy range.
- Suitable for use on internal doors in residential properties.
- Basic 3 lever cut key.

## **Finish**

• Satin nickel (brushed finish).

## **Dimensions**

- Available in two sizes
- 64mm case depth (44mm backset).
- 76mm case depth (57mm backset).



SIDE PROFILE END PROFILE STRIKE PLATE

Item Code	Lock Case Depth (A)	Backset To Keyhole (B)
43933,1	64mm	44mm

43933.2	76mm	57mm

## **Standards This Product Conforms To**

- Lock case tested and passed to BS EN 12209. The British / European standard requirements and test methods covering locks and latches. Classification number **2H810F1KD2A**.
- Tested and passed to BS EN 1634 the British / European standard for determining the fire resistance of door and shutter assemblies including hardware. Assessed for use on 30 minute and 1 hour timber fire doors FD30 / FD60.- Intumescent lock case liners required (sold separately).
- Certifire approved.
- CE Marked / UKCA Marked.
- Declaration of performance (DoP) please see the additional information tab to download the certificate.

# **Options Available To Order**

- This lock is also available to order with radius (rounded shape) forend and strike plates. Please contact us for lead times and prices.
- Intumescent sheets and lock case liners are available. Please see our intumescent fire rated products category for more details.

#### **Unit Of Sale**

• Each - (1 x lock case supplied with forend, strike plate and 2 keys).

#### **Products in this set**



43993.1 - 3 Lever Economy Mortice Sash Lock - CE / UKCA Marked - Fire Rated - Certifire Approved - CE / UKCA Marked - 64mm Case Depth (44mm Backset) - Satin Nickel



43993.2 - 3 Lever Economy Mortice Sash Lock - CE / UKCA Marked - Fire Rated - Certifire Approved - CE / UKCA Marked - 76mm Case Depth (57mm Backset) - Satin Nickel