

G Johns & Sons Ltd Unit D Westside Business Centre Flex Meadow Harlow, Essex CM19 5SR

# Architectural Quality DIN Style Euro Profile Sash Lock - CE / UKCA Marked - Fire Rated - Certifire Approved - Matt Bronze (Powder Coated)

#### **Product Images**



- Euro profile DIN standard mortice sash lock.
- Case size 150mm x 85mm.
- 60mm backset 72mm euro to spindle centers.
- Satisfies BS 8300 and Approved Doc M (ADM). Suitable for use in public and commercial buildings.
- For use on doors that require lever door handles and need to be locked via a euro profile cylinder.
- Must be used in conjunction with some form of door handle and a euro cylinder.

#### **Operation**

- Latch is withdrawn via a lever handle from either side of the door. (handles sold separately).
- Deadbolt is locked and un-locked via a Euro profile cylinder.
- One single turn of the key or thumb-turn on the Euro cylinder will completely throw the 20mm dead bolt.

#### **Features**

- Heavy duty lock case.
- Solid stainless steel deadbolt and latch.
- Dual latch springing spring strength can be adjusted on site to suit sprung or un-sprung lever furniture.
- Bolt through facility for bolt together fixing of lever handles and accessories at 38mm centers.
- Solid investment cast 8mm x 8mm spindle follower (to suit standard UK size spindles).
- 20mm bolt throw with a single turn of a key.
- 10 year mechanical guarantee as standard.
- Patented Easy turn latch reversal mechanism. Latch can be reversed on site without taking the lock case apart.
- Reversible and adjustable strike plate.
- Complete with black plastic frame box keep to sit behind the strike plate.

#### **Finish**

Matt bronze

## **Dimensions**



Item Code Lock Case Depth (A)Backset To Keyhole (B)Spindle To Euro centers (C)

44771.1

85mm

60mm

72mm

## **Standards This Product Conforms To**

- Lock case tested and passed to BS EN 12209. The British / European standard requirements and test methods covering locks and latches. Classification number 3H810F3BA20.
- Tested and passed to BS EN 1634 the British / European standard for determining the fire resistance of door and shutter assemblies including hardware. Assessed for use on 30 minute and 1 hour timber fire doors FD30 / FD60.- Intumescent lock case liners required (sold separately).
- Certifire approved.
- CE Marked / UKCA Marked.

• Declaration of performance (DoP) - please see the additional information tab to download the certificate.

## **Options Available To Order**

• Intumescent lock case liners to suit the E\*S DIN standard lock range are available. Please see our intumescent fire rated products category.

### **Unit Of Sale**

• Each - (1 x lock case supplied with forend, strike plate and black plastic back box).

#### **Products in this set**



44771.1 - Architectural Quality DIN Style Euro Profile Sash Lock - CE / UKCA Marked - Fire Rated - Certifire Approved - 85mm Case Depth (60mm backset) - 72mm Euro Centres - Matt Bronze (Powder Coated)