

G Johns & Sons Ltd Unit D Westside Business Centre Flex Meadow Harlow, Essex CM19 5SR www.gjohns.co.uk 020 8360 7771 sales@gjohns.co.uk VAT No: GB232661872 Company No: 00384076

Architectural Quality DIN Style Bathroom Mortice Lock - CE / UKCA Marked - Fire Rated - Certifire Approved - Matt Black

Product Images



- Euro profile DIN standard bathroom mortice lock.
- 5mm follower for use with standard UK bathroom snib turn & release system
- Case size 150mm x 85mm.
- 60mm backset with 78mm centers between the lever spindle hole and the bathroom spindle hole.
- Satisfies BS 8300 and Approved Doc M (ADM). Suitable for use in public and commercial buildings.
- For use on bathroom and WC doors that require lever door handles and need to be locked via a snib turn & release system.

Operation

- Latch is withdrawn via a lever handle from either side of the door. (handles sold separately).
- Deadbolt is thrown and withdrawn (locked & unlocked) via a bathroom snib turn & emergency release set (sold separately).
- Suitable for use on inward or outward opening doors.

Features

- Heavy duty lock case.
- Solid stainless steel latch and deadbolt.
- Dual latch springing spring strength can be adjusted on site to suit sprung or un-sprung lever furniture.
- Bolt through facility for bolt together fixing of lever handles and accessories at 38mm centers.
- Solid investment cast spindle followers.
- 10 year mechanical guarantee as standard.
- Patented Easi-T latch reversal mechanism. Latch can be reversed on site without taking the lock case apart.
- Reversible and adjustable strike plate.
- Complete with black plastic frame box keep to sit behind the strike plate.

Finish

Matt black

Dimensions



Item Code Lock Case Depth (A)Backset To Keyhole (B)Spindle To Spindle centers (C)

44774.1 85mm 60mm 78mm

Standards This Product Conforms To

- Lock case tested and passed to BS EN 12209. The British / European standard requirements and test methods covering locks and latches. Classification number 3H810F-BG20.
- Tested and passed to BS EN 1634 the British / European standard for determining the fire resistance of door and shutter assemblies including hardware. Assessed for use on 30 minute and 1 hour timber fire doors FD30 / FD60.- Intumescent lock case liners required (sold separately).
- Certifire approved.
- CE Marked / UKCA Marked.
- Declaration of performance (DoP) please see the additional information tab to download the certificate.

Options Available To Order

• Intumescent lock case liners to suit the E*S DIN standard lock range are available. Please see our intumescent fire rated products category.

Extra Items Required For This Lock

- Lever door handles (half set required for the inside of the door).
- A turn & emergency release set (used to lock and unlock the door).

Rebate Kit For Double Rebated Doors

• There is currently **no** matching polished finish rebate kit available to suit this lock.

Unit Of Sale

• Each - (1 x lock case supplied with forend, strike plate and black plastic back box).

Products in this set

×

44774.1 - Architectural Quality DIN Style Bathroom Mortice Lock - CE / UKCA Marked - Fire Rated -Certifire Approved - 85mm Case Depth - (60mm Backset) - (78mm Centres) - Matt Black