

Harlow, Essex CM19 5SR www.gjohns.co.uk 020 8360 7771 sales@gjohns.co.uk VAT No: GB232661872 Company No: 00384076



Architectural Quality Tubular Mortice Deadbolt With 5mm Follower - CE / UKCA Marked - Fire Rated - Certifire Approved - Matt Black

Product Images



- Tubular style mortice deadbolt.
- 5mm follower designed for used with UK style bathroom turn & release sets.
- Twisting the follower a quarter is enough to throw and withdraw the deadbolt.
- 38mm bolt through holes allows turn and release sets to be bolted together for extra strength when fitted to the door.
- Architectural quality.
- Designed for use on bathroom doors, WC's and toilet doors

Operation

• Deadbolt is locked and un-locked by using a bathroom thumbturn and emergency release set.

Features

- Solid brass deadbolt with anti-saw rollers.
- Bolt through facility for bolt together fixing furniture with 38mm fixing centres.
- 5mm x 5mm spindle follower (to suit standard UK size turn & release spindles).

Security Level

- Medium security architectural range.
- Suitable for use on internal doors in residential, commercial or public buildings.

Finish

• Matt black

Dimensions



Available in four different sizes

- Available in four sizes
- 64mm case depth (44mm backset) NOTE THIS LATCH DOES NOT HAVE BOLT HOLES
- 76mm case depth (57mm backset)
- 102mm case depth (83mm backset)
- 127mm case depth (108mm backset)

	44810.1	44810.2	44810.3	44820.4	Dimension On Diagram
Overall Case Depth	64mm	76mm	102mm	127mm	А
Backset (Distance To centre Of Spindle Hole)	44mm	57mm	83mm	108mm	В
Case Height	23mm	23mm	23mm	23mm	С
Forend - Height (H) x Width (W)	60mm x 25mm	60mm x 25mm	60mm x 25mm	60mm x 25mm	D
Strike Plate - Height (H) x Width (W)	65mm x 25mm	65mm x 25mm	65mm x 25mm	65mm x 25mm	E

Options Available To Order

• Intumescent sheets and lock case liners are available. Please see our intumescent fire rated products category for details.

Unit Of Sale

• Each - (1 x latch case supplied with forend and strike plate and black back box liner).

Products in this set

