
**Architectural Quality Double Sprung Tubular Mortice Latch - CE / UKCA Marked - Fire Rated -
Certifire Approved - Matt Bronze (Powder Coated)**

Product Images



Description

- Heavy duty double sprung tubular latches.
- CE Marked / UKCA Marked.
- Fire tested to BS EN 1634-1 suitable for use on 30 minute and 60 minute FD30 and FD 60 fire doors.
- Tested to BS EN 12209-2003 the standard for mechanical locks and latches.
- Supplied with black back box for fitting behind the strike plate in the door frame.
- Heavy duty latch ideal for use with door handles fitted in residential, commercial and public buildings.
- Bolt through fixing holes at 38mm apart on the 76mm latch only - allows this latch to work in conjunction with bolt through round rose door handles.
- This latch has a heavy weight spring making it ideal for use with sprung or un-sprung door handles.

Operation

- Latch is withdrawn via a door handle from either side of the door (handles sold separately).

Features

- Double sprung - heavy weight springing with lightly sprung latch bolt (allows the door to latch into place with little friction).
- Solid brass guided latch.
- Bolt through facility for bolt together fixing lever handles and accessories at 38mm centres - **(please not the 64mm latch does not have bolt through holes).**
- 8mm x 8mm spindle follower (to suit standard UK size spindles).
- Latch can be reversed on site by twisting the latch through 180 degrees.
- Reversible frame mounted strike plate.
- Supplied with black back box for fitting behind the strike plate in the door frame.
- Suitable for use on internal doors in residential, commercial or public buildings.

Finish

- Matt bronze

Dimensions



Available in four different sizes

- Available in four sizes
- 64mm case depth (44mm backset) **NOTE THIS LATCH DOES NOT HAVE BOLT HOLES**
- 76mm case depth (57mm backset)
- 102mm case depth (83mm backset)
- 127mm case depth (108mm backset)

	44827.1	44827.2	44827.3	44827.4	Dimension On Diagram
Overall Case Depth	64mm	76mm	102mm	127mm	A
Backset (Distance To centre Of Spindle Hole)	44mm	57mm	83mm	108mm	B

Case Height	23mm	23mm	23mm	23mm	C
Forend - Height (H) x Width (W)	60mm x 25mm	60mm x 25mm	60mm x 25mm	60mm x 25mm	D
Strike Plate - Height (H) x Width (W)	65mm x 25mm	65mm x 25mm	65mm x 25mm	65mm x 25mm	E

Standards This Product Conforms To

- Lock case tested and passed to BS EN 12209. The British / European standard requirements and test methods covering locks and latches. Classification number - **A710-B00**
- Tested and passed to BS EN 1634 the British / European standard for determining the fire resistance of door and shutter assemblies including hardware. Assessed for use on 30 minute and 1 hour timber fire doors FD30 / FD60. Intumescent latch case liners required (sold separately).
- Certifire approved.
- CE Marked / UKCA Marked
- Declaration of performance (DoP) - ***please see the additional information tab to download the certificate.***

Options Available To Order

- Intumescent lock case liners to suit the DIN standard lock range are available. Please see our intumescent fire rated products category.

Unit Of Sale

- Each - (1 x latch case supplied with forend and strike plate and black back box liner).

Products in this set



44827.1 - Architectural Quality Double Sprung Tubular Mortice Latch - CE / UKCA Marked - Fire Rated - Certifire Approved - 64mm Case Depth - (44mm Backset) - Matt Bronze (Powder Coated)



44827.2 - Architectural Quality Double Sprung Tubular Mortice Latch - CE / UKCA Marked - Fire Rated - Certifire Approved - 76mm Case Depth - (57mm Backset) - Matt Bronze (Powder Coated)



44827.3 - Architectural Quality Double Sprung Tubular Mortice Latch - CE / UKCA Marked - Fire Rated - Certifire Approved - 102mm Case Depth (83mm Backset) - Matt Bronze (Powder Coated)



44827.4 - Architectural Quality Double Sprung Tubular Mortice Latch - CE / UKCA Marked - Fire Rated - Certifire Approved - 127mm Case Depth (108mm Backset) - Matt Bronze (Powder Coated)