G Johns & Sons Ltd Unit D Westside Business Centre Flex Meadow Harlow, Essex CM19 5SR

# Architectural Quality Bathroom Mortice Lock - CE / UKCA Marked - Fire Rated - Certifire Approved - Antique Brass (Lacquered)

#### **Product Images**



- Architectural quality mortice bathroom lock.
- Privacy lock for use on bathroom doors, toilets and WC doors.
- For use on doors that require door handles and need to be locked via a thumb-turn and release system.
- Must be used in conjunction with some form of door handle.

## **Operation**

- Latch is withdrawn via a lever handle from either side of the door (handles sold separately).
- Deadbolt can be locked and un-locked via a bathroom thumb-turn and release system (sold separately).
- This lock can be released from the outside in case of an emergency when used in conjunction with a turn and release.
- Only a quarter turn is required on the thumb-turn to lock and un-lock the dead bolt.

#### **Features**

- Solid brass guided latch.
- Solid brass deadbolt with anti-saw rollers.
- Medium to heavy weight springing.
- Adjustable spring strength, ideal for use with sprung or un-sprung lever furniture. (Spring strength can be adjusted by simply removing a screw
  on the edge of the lock case).
- Bolt through facility for bolt together fixing lever handles and accessories at 38mm centres.
- 8mm x 8mm spindle follower (to suit standard UK size spindles).
- 5mm x 5mm thumb-turn spindle follower (to suit standard UK size turn and release systems).
- Patented Easi-T latch reversal mechanism the latch can be reversed on site without taking the lock case apart.
- Reversible and adjustable strike plate.

## **Security Level**

- Medium security architectural range.
- Suitable for use on internal doors in residential, commercial or public buildings.
- Privacy lock.

#### **Finish**

Antique brass

### **Dimensions**

- Available in two sizes
- 64mm case depth (44mm backset).
- 76mm case depth (57mm backset).



Item Code	Lock Case Depth (A)	Backset To Keyhole (B)
44841.1	64mm	44mm

44841.2	76mm	57mm
---------	------	------

- Lever handle follower 8mm x 8mm.
- Dead bolt follower 5mm x 5mm.

#### Standards This Product Conforms To

- Lock case tested and passed to BS EN 12209. The British / European standard requirements and test methods covering locks and latches. Classification number **2H810F-BG20**.
- Tested and passed to BS EN 1634 the British / European standard for determining the fire resistance of door and shutter assemblies including hardware. Assessed for use on 30 minute and 1 hour timber fire doors FD30 / FD60.- Intumescent lock case liners required (sold separately).
- Certifire approved.
- CE Marked / UKCA Marked.
- Declaration of performance (DoP) please see the additional information tab to download the certificate.

## **Options Available To Order**

• Intumescent sheets and lock case liners are available. Please see our intumescent fire rated products category for details.

#### **Unit Of Sale**

• Each - (1 x lock case supplied with forend, strike plate and plastic back box).

#### Products in this set



44841.1 - Architectural Quality Bathroom Mortice Lock - CE / UKCA Marked - Fire Rated - Certifire Approved - 64mm Case Depth - (44mm Backset) - Antique Brass (Lacquered)



44841.2 - Architectural Quality Bathroom Mortice Lock - CE / UKCA Marked - Fire Rated - Certifire Approved - 76mm Case Depth - (57mm Backset) - Antique Brass (Lacquered)