
**Architectural Quality Bathroom Mortice Lock - CE / UKCA Marked - Fire Rated - Certifire Approved -
Matt Bronze (Powder Coated)**

Product Images



- Architectural quality mortice bathroom lock.
- Privacy lock for use on bathroom doors, toilets and WC doors.
- For use on doors that require door handles and need to be locked via a thumb-turn and release system.
- Must be used in conjunction with some form of door handle.

Operation

- Latch is withdrawn via a lever handle from either side of the door (handles sold separately).
- Deadbolt can be locked and un-locked via a bathroom thumb-turn and release system (sold separately).
- This lock can be released from the outside in case of an emergency when used in conjunction with a turn and release.
- Only a quarter turn is required on the thumb-turn to lock and un-lock the dead bolt.

Features

- Solid brass guided latch.
- Solid brass deadbolt with anti-saw rollers.
- Medium to heavy weight springing.
- Adjustable spring strength, ideal for use with sprung or un-sprung lever furniture. (Spring strength can be adjusted by simply removing a screw on the edge of the lock case).
- Bolt through facility for bolt together fixing lever handles and accessories at 38mm centres.
- 8mm x 8mm spindle follower (to suit standard UK size spindles).
- 5mm x 5mm thumb-turn spindle follower (to suit standard UK size turn and release systems).
- Patented Easi-T latch reversal mechanism - the latch can be reversed on site without taking the lock case apart.
- Reversible and adjustable strike plate.

Security Level

- Medium security architectural range.
- Suitable for use on internal doors in residential, commercial or public buildings.
- Privacy lock.

Finish

- Matt bronze

Dimensions

- Available in two sizes
- 64mm case depth (44mm backset).
- 76mm case depth (57mm backset).



Item Code	Lock Case Depth (A)	Backset To Keyhole (B)
44843.1	64mm	44mm

44843.2	76mm	57mm
---------	------	------

- Lever handle follower - 8mm x 8mm.
- Dead bolt follower - 5mm x 5mm.

Standards This Product Conforms To

- Lock case tested and passed to BS EN 12209. The British / European standard requirements and test methods covering locks and latches. Classification number - **2H810F-BG20**.
- Tested and passed to BS EN 1634 the British / European standard for determining the fire resistance of door and shutter assemblies including hardware. Assessed for use on 30 minute and 1 hour timber fire doors FD30 / FD60.- Intumescent lock case liners required (sold separately).
- Certifire approved.
- CE Marked / UKCA Marked.
- Declaration of performance (DoP) - ***please see the additional information tab to download the certificate.***

Options Available To Order

- Intumescent sheets and lock case liners are available. Please see our intumescent fire rated products category for details.

Unit Of Sale

- Each - (1 x lock case supplied with forend, strike plate and plastic back box).

Products in this set



44843.1 - Architectural Quality Bathroom Mortice Lock - CE / UKCA Marked - Fire Rated - Certifire Approved - 64mm Case Depth - (44mm Backset) - Matt Bronze (Powder Coated)



44843.2 - Architectural Quality Bathroom Mortice Lock - CE / UKCA Marked - Fire Rated - Certifire Approved - 76mm Case Depth - (57mm Backset) - Matt Bronze (Powder Coated)