

G Johns & Sons Ltd Unit D Westside Business Centre Flex Meadow Harlow, Essex CM19 5SR

Architectural Quality DIN Style Euro Profile Sash Lock - CE / UKCA Marked - Fire Rated - Certifire Approved - Matt Black

Product Images



- Euro profile DIN standard mortice sash lock.
- Case size 150mm x 85mm.
- 60mm backset 72mm euro to spindle centers.
- Satisfies BS 8300 and Approved Doc M (ADM). Suitable for use in public and commercial buildings.
- For use on doors that require lever door handles and need to be locked via a euro profile cylinder.
- Must be used in conjunction with some form of door handle and a euro cylinder.

Operation

- Latch is withdrawn via a lever handle from either side of the door. (handles sold separately).
- Deadbolt is locked and un-locked via a Euro profile cylinder.
- One single turn of the key or thumb-turn on the Euro cylinder will completely throw the 20mm dead bolt.

Features

- Heavy duty lock case.
- Solid stainless steel deadbolt and latch.
- Dual latch springing spring strength can be adjusted on site to suit sprung or un-sprung lever furniture.
- Bolt through facility for bolt together fixing of lever handles and accessories at 38mm centers.
- Solid investment cast 8mm x 8mm spindle follower (to suit standard UK size spindles).
- 20mm bolt throw with a single turn of a key.
- 10 year mechanical guarantee as standard.
- Patented Easy turn latch reversal mechanism. Latch can be reversed on site without taking the lock case apart.
- Reversible and adjustable strike plate.
- Complete with black plastic frame box keep to sit behind the strike plate.

Finish

Matt black

Dimensions



Item Code Lock Case Depth (A)Backset To Keyhole (B)Spindle To Euro centers (C)

44858.1

85mm

60mm

72mm

Standards This Product Conforms To

- Lock case tested and passed to BS EN 12209. The British / European standard requirements and test methods covering locks and latches. Classification number **3M810F3BA00**.
- Tested and passed to BS EN 1634 the British / European standard for determining the fire resistance of door and shutter assemblies including hardware. Assessed for use on 30 minute and 1 hour timber fire doors FD30 / FD60.- Intumescent lock case liners required (sold separately).
- Certifire approved.
- CE Marked / UKCA Marked.
- Declaration of performance (DoP) please see the additional information tab to download the certificate.

Options Available To Order

• Intumescent lock case liners to suit the E*S DIN standard lock range are available. Please see our intumescent fire rated products category.

Unit Of Sale

• Each - (1 x lock case supplied with forend, strike plate and black plastic back box).

Products in this set



44858.1 - Architectural Quality DIN Style Euro Profile Sash Lock - CE / UKCA Marked - Fire Rated - Certifire Approved - 85mm Case Depth (60mm backset) - 72mm Euro Centres - Matt Black