

www.gjohns.co.uk 020 8360 7771 sales@gjohns.co.uk VAT No: GB232661872 Company No: 00384076



Richmond Elite Light Switches & Socket Range - Low Profile Plate With Squared Edges - Antique Brass (Gloss Lacquered)

Harlow, Essex CM19 5SR

£0.00 exc VAT: £0.00

Product Images



Please see the product attachments tab below, to download the price list for this range

Please give us a call or email to place an order.

Description

- Richmond Elite low profile plate light switches, dimmers and sockets.
- Semi raised plate with squared edges LP91 design.
- 5mm thick plate.

Finish

- Antique brass finish plate.
- Matching antique brass switches with black trim

Sizes

- Single plate 88mm x 88mm.
- Double plate 148mm x 88mm.

Specials

• If you're unable to find switch of socket you require in the list below, please contact us as we're able to produce a wide range of specials.

Rocker Switches - 10amp - 25mm Box Depth Required












- 2 Gang 2 Way Rocker Switch
- 3 Gang 2 Way Rocker Switch
- 4 Gang 2 Way Rocker Switch
- 1 Gang Intermediate Rocker Switch

Dolly Toggle Switches - 10amp - 35mm Box Depth Required












- 1 Gang 2 Way Dolly Toggle Switch
- 2 Gang 2 Way Dolly Toggle Switch
- 3 Gang 2 Way Dolly Toggle Switch
- 4 Gang 2 Way Dolly Toggle Switch
- 1 Gang Intermediate Dolly Toggle Switch

Dimer Switches - 35mm Box Depth Required











- 1 Gang Dimmer Switch 250 Watts
- 1 Gang Dimmer Switch 400 Watts
- 1 Gang Dimmer Switch Trailing Edge For LED Bulbs
- 2 Gang Dimmer Switch 250 Watts
- 2 Gang Dimmer Switch 400 Watts
- 2 Gang Dimmer Switch Trailing Edge For LED Bulbs
- 3 Gang Dimmer Switch 250 Watts
- 3 Gang Dimmer Switch 400 Watts
- 3 Gang Dimmer Switch Trailing Edge For LED Bulbs
- 4 Gang Dimmer Switch 250 Watts
- 4 Gang Dimmer Switch 400 Watts
- 4 Gang Dimmer Switch Trailing Edge For LED Bulbs

Switched Power Switches - 13amp - 35mm Box Depth Required







- Single Switched Socket
- Double Switched Socket
- Double Switched Socket With USB Chargers (1x 1amp USB and 1 x 2amp USB)

Fused Spurs - 13amp - 35mm Box Depth Required











- Fused Spur
- Switched Fused Spur
- Switched Fused Spur With Neon Indicator
- Switched Fused Spur With Neon & Flex Outlet

Euro Module Plates








- 1 Module Euro Plate
- 2 Module Euro Plate
- 4 Module Euro Plate

Cooker Switches - 45amp - 35mm - 48mm Box Depth Required











- Double Pole Switch
- Double Pole Switch With Neon Indicator
- Cooker Switch (Single Plate)
- Cooker Switch With 13amp Single Socket







- Triple Pole Fan Isolation Switch 6amp 25mm Box Depth
- Round 3 Pin Socket (Unswitched) 5amp 35mm Box Depth
- Shaver Socket With Dual Output 110v / 240v 48mm Box Depth

TV & Satellite Sockets - 35mm Box Depth Required















- Single Non-Isolated TV / Coaxial Socket
- Single Isolated TV / Coaxial Socket
- Twin Non-Isolated TV / Coaxial Socket
- TV/FM Diplexed Coaxial Socket
- Satellite Socket
- TV / Satellite Socket



- 1 Gang Secondary Telephone Line Socket
- 1 Gang Master Telephone Line Socket
- 2 Gang Secondary Telephone Line Socket
- 2 Gang Master Telephone Line Socket
- 1 Gang RJ45 Data Socket
- 2 Gang RJ45 Data Socket
- 1 Gang RJ11 Socket

Blanking Plates



- Single Section Blank Plate
- Double Section Blank Plate

Important Information:

• USB sockets are fitted with 1 x 1amp USB charger and 1 x 2amp USB charger.

Trailing Edge Dimmers for LED bulbs

- Maximum of 10 LED lamps per module.
- Minimum load 0 W per module. Maximum load 120 W per module.
- Suitable for most quality dimmable LED lamps.
- Compatibility is not guaranteed with all LED bulbs.

Box Depth

- When installing electrical accessories it is important to ensure that wall boxes of adequate depth are used.
- The box depth should comfortably accommodate the accessory and its connecting cables, and is particularly important with flat plate ranges and power accessories.
- The product selector table above gives recommended box depths for normal installation conditions.