

G Johns & Sons Ltd Unit D Westside Business Centre Flex Meadow Harlow, Essex CM19 5SR www.gjohns.co.uk 020 8360 7771 sales@gjohns.co.uk VAT No: GB232661872 Company No: 00384076

# Architectural Quality Tubular Mortice Deadbolt With 5mm Follower - CE / UKCA Marked - Fire Rated - Certifire Approved - Polished Brass PVD Plated

#### **Product Images**





#### **Description**

- Tubular style mortice deadbolt.
- Supplied with a PVD brass (shiny finish) forend and frame mounted receiver plate including black plastic back box.
- 5mm follower designed for used with UK style bathroom turn & release sets.
- Twisting the follower a quarter is enough to throw and withdraw the deadbolt.
- 38mm bolt through holes allows turn and release sets to be bolted together for extra strength when fitted to the door.
- Architectural quality.

- Designed for use on bathroom doors, WC's and toilet doors
- Can also be used as a heavy duty security bolt for front and back doors when used in conjunction with the SDB5010EB key and escutcheon pack.

# **Operation**

• Deadbolt is locked and un-locked by using a bathroom thumbturn and emergency release set.

#### **Features**

- Solid brass deadbolt with anti-saw rollers.
- Bolt through facility for bolt together fixing furniture with 38mm fixing centres.
- 5mm x 5mm spindle follower (to suit standard UK size turn & release spindles).

# **Security Level**

- Medium security architectural range.
- Suitable for use on internal doors in residential, commercial or public buildings.


### **Finish**

PVD brass.

### **Alternative Finishes Available**

- Polished stainless steel.
- Satin stainless steel.
- Florentine bronze.

## **Dimensions**



Item Code	Case Depth (A)	Backset To Follower (B)
20081.4	64mm	44mm
20081.1	76mm	57mm
20081.2	102mm	82mm
20081.3	125mm	108mm

### Standards This Product Conforms To

- Lock case tested and passed to BS EN 12209. The British / European standard requirements and test methods covering locks and latches. Classification number - 3H810F-BG00.
- Tested and passed to BS EN 1634 the British / European standard for determining the fire resistance of door and shutter assemblies including hardware. Assessed for use on 30 minute and 1 hour timber fire doors FD30 / FD60.- Intumescent lock case liners required (sold separately).
- Certifire approved.
- CE Marked / UKCA Marked.
- Declaration of performance (DoP) please see the additional information tab to download the certificate.

### **Options Available To Order**

- This dead bolt is also available to order with radius (rounded shape) forend and receiver plates. Please contact us for lead times and prices.
- Intumescent sheets and lock case liners are available. Please see our intumescent fire rated products category for details.

### Rebate Kit For Double Rebated Doors

No rebate kit available to suit this dead bolt.

### **Unit Of Sale**

• Each - (1 x dead bolt supplied with forend, receiver plate and plastic back box).

#### Products in this set

