





## Description

---

Our leaf & half lobby / corridor kit is ideal to specify or purchase for doors in blocks of flats, offices, schools, hotels and hospitals.

This key locking kit is supplied with a pull handle and push plate to open the door with and a double Euro profile cylinder to allow the door to be locked. The half door is locked shut via lever action flush bolts.

High performance ironmongery including grade 14, concealed nylon bearing fire rated hinges (maintenance free with no grease) and a high quality EN1154 2-5 power overhead door closer.

Products tested for use on 30 minute FD30 and 60 minute FD60 timber fire rated doors and frames.

- Our FD30 kit is supplied with **1mm** thick intumescent hinge pad liners
- Our FD60 kit is supplied with **2mm** thick intumescent hinge pad liners.

Items supplied in our FD30 fire door kit:

- 6 x (3 x Pairs) - 41734.1 - Concealed Nylon Bearing Grade 14 Hinges - Self Lubricating - CE Marked / UKCA Marked - Fired Rated - Certifire Approved - 160kg Weight Limit - 102mm x 76mm - Satin Stainless Steel
- 12 x 40897.1 - Intumescent Hinge Pad Liners - 100mm x 30mm x 1mm - For Use On FD30 Fire Rated Doors - Monoammonium Phosphate
- 1 x 49026.1 - Slimline Overhead Door Closer With Backcheck - CE Marked / UKCA Marked - Fire Rated - Certifire Approved - EN1154 Power Size 2-5 - Adjustable Via Spring - 240mm x 69mm x 49mm - Satin Stainless Steel
- 1 x 30894.1 - Architectural Quality DIN Style Euro Profile Mortice Deadlock - CE Marked / UKCA Marked - Fire Rated - Certifire Approved - 85mm Case Depth (60mm Backset) - Satin Stainless Steel
- 1 x 31211.1 - FD30 / FD60 Intumescent Pack To Suit DIN Style Lock
- 1 x 30677.4 - 5 Pin - Euro Profile Cylinder - Key/Key - Satin Chrome - 70mm
- 2 x 40810.2 - Lever Action Flush Bolts - Suitable For Use On FD30 / FD60 Fire Doors - 200mm x 20mm - Satin Stainless Steel
- 2 x 41667.1 - 2mm Intumescent Kit To Suit Flush Bolts Up To 200mm Long For FD30 / FD60 Doors
- 1 x 31212.3 - D Shaped Pull Handle - Bolt Through Fixing - Satin Stainless Steel - 300mm Centres x 19mm Diameter - Suitable For Use With FD30 / FD60 Fire Doors
- 1 x 20580.2 - Radius Corner Finger Plate - Satin Stainless Steel - 350mm x 75mm - Suitable For Use With FD30 / FD60 Fire Doors
- 2 x 41087.1 - Euro Profile Escutcheon - Suitable For Use On FD30 / FD60 Fire Doors - 52mm x 7mm - Satin Stainless Steel
- 2 x 20651.2 - Fire Door Keep Shut Circular Screw Fix Sign - Satin Stainless Steel With Blue Background
- 20650.2 - Fire Door Keep Locked - Circular Screw Fix Sign - Satin Stainless Steel Edge With Blue Background

Items supplied in our FD60 fire door kit:

- 6 x (3 x Pairs) - 41734.1 - Concealed Nylon Bearing Grade 14 Hinges - Self Lubricating - CE Marked / UKCA Marked - Fired Rated - Certifire Approved - 160kg Weight Limit - 102mm x 76mm - Satin Stainless Steel
- 12 x 40897.2 - Intumescent Hinge Pad Liners - 100mm x 30mm x 2mm - For Use On FD60 Fire Rated Doors - Monoammonium Phosphate
- 1 x 49026.1 - Slimline Overhead Door Closer With Backcheck - CE Marked / UKCA Marked - Fire Rated - Certifire Approved - EN1154 Power Size 2-5 - Adjustable Via Spring - 240mm x 69mm x 49mm - Satin Stainless Steel
- 1 x 30894.1 - Architectural Quality DIN Style Euro Profile Mortice Deadlock - CE Marked / UKCA Marked - Fire Rated - Certifire Approved - 85mm Case Depth (60mm Backset) - Satin Stainless Steel
- 1 x 31211.1 - FD30 / FD60 Intumescent Pack To Suit DIN Style Lock
- 1 x 30677.4 - 5 Pin - Euro Profile Cylinder - Key/Key - Satin Chrome - 70mm
- 2 x 40810.2 - Lever Action Flush Bolts - Suitable For Use On FD30 / FD60 Fire Doors - 200mm x 20mm - Satin Stainless Steel
- 2 x 41667.1 - 2mm Intumescent Kit To Suit Flush Bolts Up To 200mm Long For FD30 / FD60 Doors
- 1 x 31212.3 - D Shaped Pull Handle - Bolt Through Fixing - Satin Stainless Steel - 300mm Centres x 19mm Diameter - Suitable For Use With FD30 / FD60 Fire Doors
- 1 x 20580.2 - Radius Corner Finger Plate - Satin Stainless Steel - 350mm x 75mm - Suitable For Use With FD30 / FD60 Fire Doors
- 2 x 41087.1 - Euro Profile Escutcheon - Suitable For Use On FD30 / FD60 Fire Doors - 52mm x 7mm - Satin Stainless Steel
- 2 x 20651.2 - Fire Door Keep Shut Circular Screw Fix Sign - Satin Stainless Steel With Blue Background
- 20650.2 - Fire Door Keep Locked - Circular Screw Fix Sign - Satin Stainless Steel Edge With Blue Background

Please note although the above items have been fire tested and where required CE/ UKCA Marked, it's important to check the limitations or requirements of the fire test evidence for the fire door you are planning to install. Please call or email for further information.

Fire test certificates can be viewed and downloaded in the "Product Attachments Tab"

Items not included within this kit but may be required:

- Floor mounted door stop.
- Wall mounted door stop.
- Finger guards (commonly used in schools, hotels and hospitals).

## Products in this set

---



**49331.1 - Leaf & Half Key Locking Door Lobby / Corridor Ironmongery Kit - For 30 Minute FD30 Fire Rated Doors - Satin Stainless Steel Ironmongery**



**49331.2 - Leaf & Half Key Locking Door Lobby / Corridor Ironmongery Kit - For 60 Minute FD60 Fire Rated Doors - Satin Stainless Steel Ironmongery**