

Flex Meadow Harlow, Essex CM19 5SR www.gjohns.co.uk 020 8360 7771 sales@gjohns.co.uk VAT No: GB232661872 Company No: 00384076



Single Door With Mechanical Combination Digi Lock - Ironmongery Kit - Suitable For FD30 & FD60 Fire Doors - Satin Stainless Steel Ironmongery

Product Images











Description

Our single door kit with push button Codelock is ideal to specify or purchase for single doors in blocks of flats, offices, schools, hotels and hospitals.

High performance ironmongery including grade 14, concealed nylon bearing fire rated hinges (maintenance free with no grease) and a high quality EN1154 2-5 power overhead door closer.

Products tested for use on 30 minute FD30 and 60 minute FD60 timber fire rated doors and frames.

- Our FD30 kit is supplied with **1mm** thick intumescent hinge pad liners
- Our FD60 kit is supplied with **2mm** thick intumescent hinge pad liners.

Items supplied in our FD30 fire door kit:

- 3 x (1.5 Pairs) 41734.1 Concealed Nylon Bearing Grade 14 Hinges Self Lubricating CE Marked / UKCA Marked Fired Rated Certifire Approved 160kg Weight Limit 102mm x 76mm Satin Stainless Steel
- 6 x 40897.1 Intumescent Hinge Pad Liners 100mm x 30mm x 1mm For Use On FD30 Fire Rated Doors Monoammonium Phosphate
- 1 x 49026.1 Slimline Overhead Door Closer With Backcheck CE Marked / UKCA Marked Fire Rated Certifire Approved EN1154 Power Size 2-5 Adjustable Via Spring 240mm x 69mm x 49mm Satin Stainless Steel
- 1 x 40178.1 Codelocks CL410 Medium Duty Mechanical Digital Combination Lock With Lever Handle Supplied With 60mm Backset Latch Satin Silver
- 1 x 44877.1 Intumescent Kit To Suit Codelocks Standard Digital Locks
- 2 x 20651.2 Fire Door Keep Shut Circular Screw Fix Sign Satin Stainless Steel With Blue Background.

Items supplied in our FD60 fire door kit:

- 3 x (1.5 Pairs) 41734.1 Concealed Nylon Bearing Grade 14 Hinges Self Lubricating CE Marked / UKCA Marked Fired Rated Certifire Approved 160kg Weight Limit 102mm x 76mm Satin Stainless Steel
- 6 x 40897.2 Intumescent Hinge Pad Liners 100mm x 30mm x 2mm For Use On FD60 Fire Rated Doors Monoammonium Phosphate
- 1 x 49026.1 Slimline Overhead Door Closer With Backcheck CE Marked / UKCA Marked Fire Rated Certifire Approved EN1154 Power Size 2-5 Adjustable Via Spring 240mm x 69mm x 49mm Satin Stainless Steel
- 1 x 40178.1 Codelocks CL410 Medium Duty Mechanical Digital Combination Lock With Lever Handle Supplied With 60mm Backset Latch Satin Silver
- 1 x 44877.1 Intumescent Kit To Suit Codelocks Standard Digital Locks
- $\bullet \ \ 2 \ x \ 20651.2 \ \ Fire \ Door \ Keep \ Shut \ Circular \ Screw \ Fix \ Sign \ \ Satin \ Stainless \ Steel \ With \ Blue \ Background.$

Please note although the above items have been fire tested and where required CE/ UKCA Marked, it's important to check the limitations or requirements of the fire test evidence for the fire door you are planning to install. Please call or email for further information.

Fire test certificates can be viewed and downloaded in the "Product Attachments Tab"

Items not included within this kit but may be required:

- Floor mounted door stop.
- Wall mounted door stop.
- Finger guards (commonly used in schools, hotels and hospitals).

Products in this set



49351.1 - Single Door With Mechanical Combination Digi Lock - Ironmongery Kit - For 30 Minute FD30 Fire Rated Doors - Satin Stainless Steel Ironmongery



49351.2 - Single Door With Mechanical Combination Digi Lock - Ironmongery Kit - For 60 Minute FD60 Fire Rated Doors - Satin Stainless Steel Ironmongery