



Description

Our single non-locking room door kit is ideal to specify or purchase for single doors in blocks of flats, offices, schools, hotels and hospitals.

This kit is supplied with a heavy duty DIN style mortice latch, and a pair of grade 4 return to door lever handles.

High performance ironmongery including grade 14, concealed nylon bearing fire rated hinges (maintenance free with no grease) and a high quality EN1154 2-5 power overhead door closer.

Products tested for use on 30 minute FD30 and 60 minute FD60 timber fire rated doors and frames.

- Our FD30 kit is supplied with **1mm** thick intumescent hinge pad liners
- Our FD60 kit is supplied with **2mm** thick intumescent hinge pad liners.

Items supplied in our FD30 fire door kit:

- 3 x (1.5 Pairs) - 41734.1 - Concealed Nylon Bearing Grade 14 Hinges - Self Lubricating - CE Marked / UKCA Marked - Fire Rated - Certifire Approved - 160kg Weight Limit - 102mm x 76mm - Satin Stainless Steel
- 6 x 40897.1 - Intumescent Hinge Pad Liners - 100mm x 30mm x 1mm - For Use On FD30 Fire Rated Doors - Monoammonium Phosphate
- 1 x 49026.1 - Slimline Overhead Door Closer With Backcheck - CE Marked / UKCA Marked - Fire Rated - Certifire Approved - EN1154 Power Size 2-5 - Adjustable Via Spring - 240mm x 69mm x 49mm - Satin Stainless Steel
- 1 x 30897.1 - Architectural Quality DIN Style Mortice Latch - CE Marked / UKCA Marked - Fire Rated - Certifire Approved - 85mm Case Depth

- (60mm Backset) - Satin Stainless Steel
- 1 x 31211.1 - FD30 / FD60 Intumescent Pack To Suit DIN Style Lock
- 1 x pair 43511.1 - Return To Door Safety Design Round Rose Lever Handles Only - Heavy Duty Grade 4 Collection BS800 / ADM Compliant - Satin Stainless Steel (Grade 316)
- 2 x 20651.2 - Fire Door Keep Shut Circular Screw Fix Sign - Satin Stainless Steel With Blue Background

Items supplied in our FD60 fire door kit:

- 3 x (1.5 Pairs) - 41734.1 - Concealed Nylon Bearing Grade 14 Hinges - Self Lubricating - CE Marked / UKCA Marked - Fired Rated - Certifire Approved - 160kg Weight Limit - 102mm x 76mm - Satin Stainless Steel
- 6 x 40897.2 - Intumescent Hinge Pad Liners - 100mm x 30mm x 2mm - For Use On FD60 Fire Rated Doors - Monoammonium Phosphate
- 1 x 49026.1 - Slimline Overhead Door Closer With Backcheck - CE Marked / UKCA Marked - Fire Rated - Certifire Approved - EN1154 Power Size 2-5 - Adjustable Via Spring - 240mm x 69mm x 49mm - Satin Stainless Steel
- 1 x 30897.1 - Architectural Quality DIN Style Mortice Latch - CE Marked / UKCA Marked - Fire Rated - Certifire Approved - 85mm Case Depth (60mm Backset) - Satin Stainless Steel
- 1 x 31211.1 - FD30 / FD60 Intumescent Pack To Suit DIN Style Lock
- 1 x pair 43511.1 - Return To Door Safety Design Round Rose Lever Handles Only - Heavy Duty Grade 4 Collection BS800 / ADM Compliant - Satin Stainless Steel (Grade 316)
- 2 x 20651.2 - Fire Door Keep Shut Circular Screw Fix Sign - Satin Stainless Steel With Blue Background

Please note although the above items have been fire tested and where required CE/ UKCA Marked, it's important to check the limitations or requirements of the fire test evidence for the fire door you are planning to install. Please call or email for further information.

Fire test certificates can be viewed and downloaded in the "Product Attachments Tab"

Items not included within this kit but may be required:

- Floor mounted door stop.
- Wall mounted door stop.
- Finger guards (commonly used in schools, hotels and hospitals).

Products in this set



49352.1 - Single Door With Non Locking Lever Handles - Ironmongery Kit - For 30 Minute FD30 Fire Rated Doors - Satin Stainless Steel Ironmongery



49352.2 - Single Door With Non Locking Lever Handles - Ironmongery Kit - For 60 Minute FD60 Fire Rated Doors - Satin Stainless Steel Ironmongery