





## Description

---

Our double cupboard door kit is ideal to specify or purchase for double storage doors in blocks of flats, offices, schools, hotels and hospitals.

This key locking kit is supplied with a Euro dead lock, Euro cylinder, flush bolts and a cylinder pull.

High performance ironmongery including grade 14, concealed nylon bearing fire rated hinges (maintenance free with no grease).

Products tested for use on 30 minute FD30 and 60 minute FD60 timber fire rated doors and frames.

- Our FD30 kit is supplied with **1mm** thick intumescent hinge pad liners
- Our FD60 kit is supplied with **2mm** thick intumescent hinge pad liners.

Items supplied in our FD30 fire door kit:

- 6 x (3 Pairs) - 41734.1 - Concealed Nylon Bearing Grade 14 Hinges - Self Lubricating - CE Marked / UKCA Marked - Fired Rated - Certifire Approved - 160kg Weight Limit - 102mm x 76mm - Satin Stainless Steel
- 12 x 40897.1 - Intumescent Hinge Pad Liners - 100mm x 30mm x 1mm - For Use On FD30 Fire Rated Doors - Monoammonium Phosphate
- 1 x 30894.1 - Architectural Quality DIN Style Euro Profile Mortice Deadlock - CE Marked / UKCA Marked - Fire Rated - Certifire Approved - 85mm Case Depth (60mm Backset) - Satin Stainless Steel
- 1 x 31211.1 - FD30 / FD60 Intumescent Pack To Suit DIN Style Lock
- 1 x 30683.1 - 5 Pin - Euro Profile Single Cylinder - Satin Chrome - 40mm
- 2 x 40810.2 - Lever Action Flush Bolts - Suitable For Use On FD30 / FD60 Fire Doors - 200mm x 20mm - Satin Stainless Steel
- 2 x 41667.1 - 2mm Intumescent Kit To Suit Flush Bolts Up To 200mm Long For FD30 / FD60 Doors
- 1 x 31259.1 - Euro Cylinder Pull - 78mm x 44mm x 3mm - Satin Stainless Steel
- 2 x 20650.2 - Fire Door Keep Locked - Circular Screw Fix Sign - Satin Stainless Steel Edge With Blue Background

Items supplied in our FD60 fire door kit:

- 6 x (3 Pairs) - 41734.1 - Concealed Nylon Bearing Grade 14 Hinges - Self Lubricating - CE Marked / UKCA Marked - Fired Rated - Certifire Approved - 160kg Weight Limit - 102mm x 76mm - Satin Stainless Steel
- 12 x 40897.2 - Intumescent Hinge Pad Liners - 100mm x 30mm x 2mm - For Use On FD60 Fire Rated Doors - Monoammonium Phosphate
- 1 x 30894.1 - Architectural Quality DIN Style Euro Profile Mortice Deadlock - CE Marked / UKCA Marked - Fire Rated - Certifire Approved - 85mm Case Depth (60mm Backset) - Satin Stainless Steel

- 1 x 31211.1 - FD30 / FD60 Intumescent Pack To Suit DIN Style Lock
- 1 x 30683.1 - 5 Pin - Euro Profile Single Cylinder - Satin Chrome - 40mm
- 2 x 40810.2 - Lever Action Flush Bolts - Suitable For Use On FD30 / FD60 Fire Doors - 200mm x 20mm - Satin Stainless Steel
- 2 x 41667.1 - 2mm Intumescent Kit To Suit Flush Bolts Up To 200mm Long For FD30 / FD60 Doors
- 1 x 31259.1 - Euro Cylinder Pull - 78mm x 44mm x 3mm - Satin Stainless Steel
- 2 x 20650.2 - Fire Door Keep Locked - Circular Screw Fix Sign - Satin Stainless Steel Edge With Blue Background

Please note although the above items have been fire tested and where required CE/ UKCA Marked, it's important to check the limitations or requirements of the fire test evidence for the fire door you are planning to install. Please call or email for further information.

Fire test certificates can be viewed and downloaded in the "Product Attachments Tab"

## Products in this set

---



**49358.1 - Double Locking Cupboard Door - Ironmongery Kit - For 30 Minute FD30 Fire Rated Doors - Satin Stainless Steel Ironmongery**



**49358.2 - Double Locking Cupboard Door - Ironmongery Kit - For 60 Minute FD60 Fire Rated Doors - Satin Stainless Steel Ironmongery**