

G Johns & Sons Ltd Unit D Westside Business Centre Flex Meadow Harlow, Essex CM19 5SR www.gjohns.co.uk 020 8360 7771 sales@gjohns.co.uk VAT No: GB232661872 Company No: 00384076

Architectural Quality Tubular Mortice Deadbolt With 5mm Follower - CE / UKCA Marked - Fire Rated - Certifire Approved - Satin Stainless Steel

Product Images





Description

- Tubular style mortice deadbolt.
- Supplied with a satin stainless steel (brushed finish) forend and frame mounted receiver plate including black plastic back box.
- 5mm follower designed for used with UK style bathroom turn & release sets.
- Twisting the follower a quarter is enough to throw and withdraw the deadbolt.
- 38mm bolt through holes allows turn and release sets to be bolted together for extra strength when fitted to the door.
- Architectural quality.

- Designed for use on bathroom doors, WC's and toilet doors
- Can also be used as a heavy duty security bolt for front and back doors when used in conjunction with the SDB5010SC key and escutcheon pack.

Operation

• Deadbolt is locked and un-locked by using a bathroom thumbturn and emergency release set.

Features

- Solid brass deadbolt with anti-saw rollers.
- Bolt through facility for bolt together fixing furniture with 38mm fixing centres.
- 5mm x 5mm spindle follower (to suit standard UK size turn & release spindles).

Security Level

- Medium security architectural range.
- Suitable for use on internal doors in residential, commercial or public buildings.


Finish

• Satin stainless steel.

Alternative Finishes Available

- Polished stainless steel.
- PVD brass.
- Florentine bronze.

Dimensions



Item Code	Case Depth (A)	Backset To Follower (B)
20858.4	64mm	44mm
20858.1	76mm	57mm
20858.2	102mm	82mm
20858.3	125mm	108mm

Standards This Product Conforms To

- Lock case tested and passed to BS EN 12209. The British / European standard requirements and test methods covering locks and latches. Classification number - 3H810F-BG00.
- Tested and passed to BS EN 1634 the British / European standard for determining the fire resistance of door and shutter assemblies including hardware. Assessed for use on 30 minute and 1 hour timber fire doors FD30 / FD60.- Intumescent lock case liners required (sold separately).
- Certifire approved.
- CE Marked / UKCA Marked.
- Declaration of performance (DoP) please see the additional information tab to download the certificate.

Options Available To Order

- This dead bolt is also available to order with radius (rounded shape) forend and receiver plates. Please contact us for lead times and prices.
- Intumescent sheets and lock case liners are available. Please see our intumescent fire rated products category for details.

Rebate Kit For Double Rebated Doors

No rebate kit available to suit this dead bolt.

Unit Of Sale

• Each - (1 x dead bolt supplied with forend, receiver plate and plastic back box).

Products in this set

