
Safety Lever To BS:8300 / ADM - Collection Silver Anodised Aluminium - Suitable For Use With FD30 / FD60 Fire Doors

Product Images





Description

- 19mm diameter tubular levers with a "return to door" design with round rose.
- Made from aluminium with a silver anodised finish known as SAA.
- Suitable for domestic or commercial use.

Inclusive Design



BS 8300 / ADM COMPLIANT

Lever Handles Tested To: FD 30 / 60 Fire Doors



BS EN 1906 : 2001



BS EN 1634

- 10mm press on rose.
- Good quality for an economy range.
- Matching SAA accessories available including Standard escutcheons (keyhole covers), Euro profile escutcheons, a bathroom turn & release set and a disabled bathroom turn and release set.

How To Order Lever Handles With A Rose


- **For Non-Locking Doors** - 1 x (Pair) Lever Handles Only




- **For Locking Doors** - 1 x (Pair) Lever Handles Only + 2 x (Each) Standard Escutcheons



- **For Euro Cylinder Locking Doors** - 1 x (Pair) Lever Handles Only + 2 x (Each) Euro Escutcheons



- **For Locking Bathroom Doors** - 1 x Pair Lever Handles Only + 1 x (Set) Turn & Emergency Release



Matching Accessories

- **Standard escutcheon** - (key hole cover to suit regular "chubb style locks")
- **Euro profile escutcheon** - (key hole cover to suit euro profile cylinders)
- **Turn & emergency release** - (a thumbturn used to lock bathroom doors, WC's and toilet doors)

Base Material

- Made from aluminium.

Finish Details

- SAA - Silver anodised aluminium.

Operation

- Both levers are sprung to ensure the lever always returns to its starting position.

Size Information

- Rose Diameter - 52mm
- Rose Thickness - 8mm
- Lever Length - 145mm
- Lever Diameter - 19mm

Spindle Size

- 8mm x 8mm square - UK Standard.

Fixings

- Press on rose.
- Concealed bolt together fixing.
- Comes supplied with M4 male and female bolt through fixings and 8mm spindle.
- Grub screw fixing to spindle for extra strength once fitted to the door.

Usage

- Suitable for residential or commercial use.
- Suitable for internal or external use.

Standards This Product Conforms To

Inclusive Design



- **BS 8300 / ADM COMPLIANT**
Inclusive design - The shape and style of these lever handles are compliant to Approved Doc M (ADM) and meet the dimensional requirements of BS 8300. These handles are suitable for use in public buildings.

Lever Handles Tested To:



- **BS EN 1906 : 2001**
Successfully type tested to the all the requirements of the European performance standard BS EN1906 2002

FD 30 / 60 Fire Doors



- **BS EN 1634**
These door handles have been included on a successful fire test to BS EN1634: Part 1 2000 - Assessed for use on 30 minute and 1 hour fire doors FD30 / FD60.

Unit Of Sale

- Lever handles are sold in pairs

Products in this set



30228.1 - Safety Lever To BS:8300 / ADM Lever Handles Only - Tested For Use With FD30 / FD60 Fire Doors - SAA - Aluminium - Pair