

G Johns & Sons Ltd Unit D Westside Business Centre Flex Meadow Harlow, Essex CM19 5SR www.gjohns.co.uk 020 8360 7771 sales@gjohns.co.uk VAT No: GB232661872 Company No: 00384076

Architectural Quality DIN Style Euro Profile Mortice Deadlock - CE / UKCA Marked - Fire Rated - Certifire Approved - Polished Stainless Steel

Product Images





Description

- 30894.1 Euro profile DIN standard mortice dead lock.
- Polished stainless steel (shiny finish).
- Case size 150mm x 85mm.
- 60mm backset
- Satisfies BS 8300 and Approved Doc M (ADM). Suitable for use in public and commercial buildings.
- For use on doors that need to be locked only and do not require a pair of lever door handles.

- Must be used in conjunction with a Euro profile cylinder (sold separately).
- Comes supplied with polished (shiny) stainless steel forend and frame mounted strike plate.

Operation

- Dead lock operated via a Euro profile cylinder (sold separately).
- One single turn of the key or thumbturn on the Euro cylinder will completely throw the 20mm dead bolt.

Features

- Heavy duty lock case and stainless steel striker plate for the door frame.
- Solid stainless steel deadbolt.
- Bolt through facility for bolt together fixing of lever handles and accessories at 38mm centers.
- 10 year mechanical guarantee as standard.
- 20mm bolt throw with a single turn of a key.
- Reversible and adjustable strike plate.
- Complete with black plastic frame box keep to sit behind the strike plate.


Finish

• Polished stainless steel - (shiny finish).

Alternative Finishes Available

- Satin stainless steel
- PVD Brass finish

Dimensions



Item Code Lock Case Depth (A)Backset To Keyhole (B)Case Height

40668.1 85mm 60mm 150mm

Standards This Product Conforms To

- Lock case tested and passed to BS EN 12209. The British / European standard requirements and test methods covering locks and latches. Classification number **3M810F3BA00**.
- Tested and passed to BS EN 1634 the British / European standard for determining the fire resistance of door and shutter assemblies including hardware. Assessed for use on 30 minute and 1 hour timber fire doors FD30 / FD60.- Intumescent lock case liners required (sold separately).
- Certifire approved.
- CE Marked / UKCA Marked.
- Declaration of performance (DoP) please see the additional information tab to download the certificate.

Options Available To Order

- This lock is also available to order with radius (rounded shape) forened and strike plates. Please contact us for lead times and prices.
- Intumescent lock case liners to suit the E*S DIN standard lock range are available. Please see our intumescent fire rated products category.

Rebate Kit For Double Rebated Doors

• There is currently **no** polished finish rebate kit for this lock.

Unit Of Sale

• Each - (1 x lock case supplied with forend, strike plate and black plastic back box).



40668.1 - Architectural Quality DIN Style Euro Profile Mortice Deadlock - CE / UKCA Marked - Fire Rated - Certifire Approved - 85mm Case Depth (60mm Backset) - Polished Stainless Steel