

G Johns & Sons Ltd Unit D Westside Business Centre Flex Meadow Harlow, Essex CM19 5SR www.gjohns.co.uk 020 8360 7771 sales@gjohns.co.uk VAT No: GB232661872 Company No: 00384076

#### Architectural Quality DIN Style Euro Profile Sash Lock - CE / UKCA Marked - Fire Rated - Certifire Approved - 60mm Backset - 72mm Centres - Polished Stainless Steel

#### **Product Images**





#### Description

- 40673.1 Euro profile DIN standard mortice sash lock.
- Polished stainless steel (shiny finish).
- Case size 150mm x 85mm.
- 60mm backset 72mm euro to spindle centers.
- Satisfies BS 8300 and Approved Doc M (ADM). Suitable for use in public and commercial buildings.
- For use on doors that require lever door handles and need to be locked via a euro profile cylinder.

- Must be used in conjunction with some form of door handle and a euro cylinder.
- Comes supplied with a polished stainless steel (shiny finish) forend and frame mounted strike plate.

# Operation

- Latch is withdrawn via a lever handle from either side of the door. (handles sold separately).
- Deadbolt is locked and un-locked via a Euro profile cylinder.
- One single turn of the key or thumb-turn on the Euro cylinder will completely throw the 20mm dead bolt.

### Features

- Heavy duty lock case and stainless steel striker plate for the door frame.
- Solid stainless steel deadbolt and latch.
- Dual latch springing spring strength can be adjusted on site to suit sprung or un-sprung lever furniture.
- Bolt through facility for bolt together fixing of lever handles and accessories at 38mm centers.
- Solid investment cast 8mm x 8mm spindle follower (to suit standard UK size spindles).
- 20mm bolt throw with a single turn of a key.
- 10 year mechanical guarantee as standard.
- Patented Easy turn latch reversal mechanism latch can be reversed on site without taking the lock case apart.
- Reversible and adjustable strike plate.
- Complete with black plastic frame box keep to sit behind the strike plate.

### Finish

• Polished stainless steel - (shiny finish)

# **Alternative Finishes Available**

- Satin stainless steel
- PVD brass

# Dimensions



Item Code Lock Case Depth (A)Backset To Keyhole (B)Spindle To Euro centers (C)

40673.1	85mm	60mm	72mm
---------	------	------	------

### **Standards This Product Conforms To**

- Lock case tested and passed to BS EN 12209. The British / European standard requirements and test methods covering locks and latches. Classification number 3H810F3BA20.
- Tested and passed to BS EN 1634 the British / European standard for determining the fire resistance of door and shutter assemblies including hardware. Assessed for use on 30 minute and 1 hour timber fire doors FD30 / FD60.- Intumescent lock case liners required (sold separately).
- Certifire approved.
- CE Marked / UKCA Marked.
- Declaration of performance (DoP) please see the additional information tab to download the certificate.

#### **Options Available To Order**

- This lock is also available to order with radius (rounded shape) forened and strike plates. Please contact us for lead times and prices.
- Intumescent lock case liners to suit the E\*S DIN standard lock range are available. Please see our intumescent fire rated products category.

# **Rebate Kit For Double Rebated Doors**

• There is currently *no* polished finish rebate kit available to suit this lock.

# **Unit Of Sale**

• Each - (1 x lock case supplied with forend, strike plate and black plastic back box).

×

40673.1 - Architectural Quality DIN Style Euro Profile Sash Lock - CE / UKCA Marked - Fire Rated -Certifire Approved - 85mm Case Depth (60mm backset) - 72mm Centres - Polished Stainless Steel